

MTB M
M-SLriLs optionÉl LtpÉnsion

3	Series model
ID04	(-ijhÉnnLI stÉnLÉrL input)
OD04	(-ijhÉnnLI stÉnLÉrL output)

4	Fixed suffix)
(N A)	(M M M M S S sLriLs optionÉl ijÉrL)
200	M sLriLs optionÉl ijÉrL
100	M sLriLs optionÉl ijÉrL
500	M sLriLs optionÉl ijÉrL

5	Fixed suffix)
BD	BD OptionÉl BD ijÉrL)
6	/ Software/Firmware customized code and other identifiers
TTTT	A Ø (N A)
PNP	SourijL tupL

3. ApplijÉIJIL moLLI

NÉmL)	MoLLI)	ApplijÉIJIL ijo	► W	=	■

MoLLI ¹	²	RÉtLÉ ÉoltÉgL poolr ²	DC é mA Ch	DigitÉl input output tupL
HCMIB-ID -BD			DC é mA Ch	DigitÉl input DC é mA Ch
HCMIB-OD -BD	DC é é	DC é é	DC é mA Ch A Ch ³	DigitÉl output DC é mA Ch A Ch ³
HCMIB-OD -BD-PNP			DC é mA Ch A Ch ³	LoÉL tupL RLsistiÉL InLuijtiÉL LÉmp loÉLs
	LPS	SELÉ		DigitÉl output DC é mA Ch A Ch ³
				LoÉL tupL RLsistiÉL InLuijtiÉL LÉmp loÉLs

NotL All moLLIs ijÉn onlu opLrÉtL unLr thL sÉfLtu LtrÉ loo ÉoltÉgL (SELÉ) proÉiLLÉ lu É limitLÉ poolr sourijL (LPS)
ihL poolr réting inLijÉtLÉ hLrL is thL mÉtimum poolr unLr full-loÉL opLrÉtion
ConsiLr thL LÓLjt of tÉmpLrÉturtL risL ÉnL LÉrÉtL Luring using

4.2 EnxiironmÉntÉl rÉquirÉmÉnts			
	ItLm		ÂpLijixijÉtions
	Altitude		

tion

[illegible]